IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Kobby Pick et al.   Art Unit: 2631
Serial No.: 10/053,490   Examiner: Phuong M. Phu
Filed: October 26, 2001
Title: METRIC CORRECTION FOR MULTI USER DETECTION, FOR LONG
             CODES DS-CDMA

Mail Stop Appeal Brief - Patents
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

BRIEF ON APPEAL

Applicant hereby files this Brief on Appeal to perfect the

Notice of Appeal filed December 16, 2005.

(1) Real Party in Interest

This case is assigned of record to Intel Corporation.

(2) Related Appeals and Interferences

There are no known related appeals and/or interferences.

(3) Status of Claims

Claims 1-28 are pending. Claims 1, 9, 19, and 24 are in

independent form. Claims 19-23 are allowed. Claims 2 and 15

02/21/2006 ZJUHAR1 00000001 10053490
01 FC:1402   500.00 OP

are objected to as dependent on a rejected independent claim.

The rejections of claims 1-18 and 24-28 are appealed.

(4)   Status of Amendments

Claims 4, 5, and 24 were amended after final rejection in

the Amendment filed on November 23, 2005. The Advisory Action

mailed December 16, 2005 indicated that these claim amendments

would be entered for purposes of appeal.

(5)   Summary of Claimed Subject Matter

In direct sequence spread spectrum transmission, a stream

of information is divided into small pieces, each of which is

allocated across the spectrum to a different signature sequence

over the same frequency channel. *See specification*, page 3,

line 12-15. With multiple users, these allocations can become

cross-correlated and the resulting interference is termed

"multiple access interference (MAI)." *See specification*, page

3, line 20-page 4, line 2. The amount of multiple access

interference can change from symbol to symbol during a direct

sequence spread spectrum transmission. *See specification*, page

4, line 1-2. However, multiple access interference is only one

contributor to the total noise that afflicts direct sequence

spread spectrum transmissions. *See, e.g., specification*, page

6, line 9-11.

Independent claim 1 relates to a method of normalizing an output of a receiver. *See, e.g.*, FIG. 2 and the written description thereof. The method includes determining a normalization factor (*see, e.g.*, FIG. 2, element 215) using a determined variance of multiple access interference (*see* FIGS. 3 and 4 and the written description thereof) and applying the normalization factor to the output of the receiver (*see* FIG. 2, element 220).

Independent claim 9 relates to a receiver. *See* FIG. 1, element 100 and the written description thereof. The receiver includes a detector to receive transmitted information and provides [sic] one or more output symbols based on the transmitted information (*see* FIG. 1, elements 110, 115) a metric correction section to normalize the one or more output symbols to obtain one or more metrics (*see* FIG. 1, element 120), and a channel decoder to receive the one or more metrics from the metric correction section (*see* FIG. 1, element 125). The normalization is based on a determined variance of multiple access interference. *See* FIGS. 3 and 4 and the written description thereof. The channel decoder utilizes the one or more metrics to decode the transmitted information. *See* FIG. 1, element 125.

Independent claim 24 relates to a method that includes receiving a symbol (*see* FIG. 1, element 110), determining a normalization factor for the symbol using a determined variance in a level of multiple access interference for the symbol (*see, e.g.*, FIG. 2, element 215, page 6, line 6-13), normalizing the symbol with the normalization factor (*see* FIG. 2, element 220), and providing the normalized symbol to a channel decoder (*see* page 6, line 14-19).

(6) Grounds of Rejection

The following grounds for rejection are presented for appeal.

I.   Independent claims 1, 9, 24 stand rejected under 35 U.S.C § 103(a) as obvious over U.S. Patent Publication No. 2002/0181624A1 to Gonzalez et al. (hereinafter "Gonzalez") and U.S. Patent No. 6,754,251 to Sriram et al. (hereinafter "Sriram").

II.   Dependent claims 5, 16, and 28 stand rejected under 35 U.S.C. § 103(a) as obvious over Gonzalez and Sriram.

(7) Argument

I. Since Gonzalez and Sriram do not Disclose Determining the Variance of Multiple Access Interference, the Obviousness Rejections of Claims 1, 9, and 24 should be Withdrawn

Claim 1, which is illustrative, relates to a method of normalizing an output of a receiver. The method includes determining a normalization factor using a determined variance of multiple access interference and applying the normalization factor to the output of the receiver.

Neither Gonzalez nor Sriram determines the variance of multiple access interference. Thus, neither Gonzalez nor Sriram describes or suggests applying a normalization factor that is determined using a determined variance of multiple access interference, as recited in claim 1.

In this regard, Gonzalez uses a final channel estimate that is the linear combination of pilot-aided and data-aided channel estimates and the variances of those estimates. *See Gonzalez,* Eq. 10 and para. [0038]. This channel estimate is based on a generic variance of noise $\square^2$. *See Gonzalez,* para. [0031]-[0032]. Gonzalez indicates that this generic variance of noise $\square^2$ is to be determined using "well-known techniques." *See Gonzalez,* para. [0030]. Gonzalez is silent as to any contribution by multiple access interference to this generic noise and as to how the variance of any contribution by multiple access interference to this generic noise variance can be determined.

Further, Gonzalez describes that this generic variance of noise provides channel estimates that are both easy to generate

and exhibit small variances. *See Gonzalez*, para. [0014]. The rejections have never established any basis why one of ordinary skill would depart from the easy and effective estimates described by Gonzalez and based on the generic variance of noise to determine a variance of multiple access interference, as recited in claims 1, 19, 24.

Sriram fails to remedy these deficiencies of Gonzalez. To begin with, Sriram also does not *determine* the variance of multiple access interference. Instead, Sriram describes that the output of his code scheme is to be *simulated* using a total variance N. *See Sriram*, col. 17, line 44 and col. 18, line 7-18. This total variance N is similar to Gonzalez' generic variance of noise $\square^2$ in that it represents the contributions of a variety of different noise sources. In particular, total variance N represent contributions from "thermal noise, inter- and intra-cell interference, and cross-correlation among different PN sequences, or their shifts." *See Sriram*, col. 18, line 16-19.

It is self-evident that simulating such a total variance does not disclose or suggest determining a variance of one contributor to that total variance. As in Gonzalez, the variance of multiple access interference is lumped in with other sources of noise, and there is no description or suggestion in

Sriram that would lead one of ordinary skill away from including

multiple access interference in with other sources to determine

a variance of multiple access interference, as recited in claims

1, 19, 24.

Since Sriram and Gonzalez neither describe nor suggest

determining of a variance of multiple access interference or

even that the determination of such a variance desirable, a

prima facie case of obviousness has not been established. The

rejections of claims 1, 19, 24, and the claims dependent

therefrom should therefore be withdrawn.

II. Since Gonzalez' Log Likelihood Ratio is not "equivalent" to the recited Log Likelihood Ratio, the Obviousness Rejections of Claims 5, 16, and 28 Should Be Withdrawn

Claims 5, 16, and 28 all involve a log likelihood ratio

(LLR) that is determined according to the equation

$LLR(n) = -\dfrac{2r(n)g(n)}{\sigma_T^2(n)}$, where r(n) is the detector output of the n^{th}

symbol, g(n) is the time varying gain associated with the

desired symbol, and $\sigma_T^2(n)$ is the total noise variance.

The rejections of claims 5, 16, and 28 all assert that

Gonzalez' LLR is "equivalent" to the claimed LLR. Applicant

respectfully disagrees.

Gonzalez' LLR is given by Gonzalez' Eq. 6, namely

$$\lambda(y) = \lambda_1(y) - \lambda_{-1}(y) = -\left(\frac{(y-a)^2}{2\sigma^2}\right) - \left(\frac{(y+a)^2}{2\sigma^2}\right) = \frac{2a^*y}{\sigma^2}$$

Applicant: Kobby Pick et al.
Serial No.: 10/053,490
Filed: October 26, 2001
Page: 8 of 19

Attorney's Docket No.: 10559-
454001 / P10771

where a is understood to be a channel estimate, y is understood

to be the received signal, and $\square^2$ is Gonzalez' generic variance

of noise. *See Gonzalez, para.* [0021], [0030].

Since Gonzalez' LLR omits variables recited in the LLR of

claims 5, 16, and 28, includes variables that are omitted from

the variables recited in the LLR of claims 5, 16, and 28, and is

understood to provide results that are different from those

provided by the LLR of claims 5, 16, and 28, the assertion that

Gonzalez' LLR is somehow "equivalent" to the LLR of claims 5,

16, and 28 is without basis.

As always, the burden of establishing a *prima facie* case of

obviousness falls on the Office. A bald assertion that

Gonzalez' LLR is somehow equivalent to the LLR of claims 5, 16,

and 28 is insufficient to meet this burden, especially since

Gonzalez specifies that the variables and results are different

from those set forth in claims 5, 16, and 28.

Moreover, even if Gonzalez' LLR were somehow equivalent to

the LLR of claims 5, 16, and 28, Gonzalez uses this LLR an input

to a confidence function for using the data aided channel

estimation.

Applicant: Kobby Pick et al.   Attorney's Docket No.:   10559-
Serial No.:   10/053,490   454001 / P10771
Filed: October 26, 2001
Page: 9 of 19

Further, Gonzalez uses his LLR as an input to a confidence function for using data aided channel estimation and not for the purposes recited in claims 5, 16, and 28. In particular, claim 5 recites that the LLR is determined in determining a normalization factor that is applied to the output of a receiver. Claim 16 recites that the LLR is determined in order to base a metric obtained by normalizing one or more output symbols. Claim 28 recites that the LLR is multiplied by an output symbol to normalize the symbol. Since none of these read on using the LLR as an input to a confidence function for using data aided channel estimation, Gonzalez neither describes nor suggests the subject matter recited in claims 5, 16, and 28.

Accordingly, a *prima facie* case of obviousness of claims 5, 16, and 28 has not been established. The rejections of claims 5, 16, 28, and the claims dependent therefrom should therefore be withdrawn.

The brief fee of $500 is enclosed. Please apply any other charges or credits to Deposit Account No. 06-1050.

Respectfully submitted,

Date: 8/16/06

_____
Scott C. Harris
Reg. No. 32,030

Fish & Richardson P.C.
12390 El Camino Real
San Diego, California 92130
Telephone: (858) 678-5070
Facsimile: (858) 678-5099

10592419.doc

(8)   Claims Appendix

1.   A method of normalizing an output of a receiver, the method comprising:

determining a normalization factor using a determined variance of multiple access interference; and

applying the normalization factor to the output of the receiver.

2.   The method of Claim 1, wherein applying the normalization factor comprises normalizing each symbol output from the receiver with a normalization factor that is independent of normalization factors of previous symbols.

3.   The method of Claim 1, further comprising obtaining a metric correction factor using the normalization factor.

4.   The method of Claim 3, further comprising providing the metric correction factor to a channel decoder.

5.   The method of Claim 1, wherein determining the normalization factor comprises determining a log likelihood ratio (LLR) according to the following equation:

$$LLR(n) = -\frac{2r(n)g(n)}{\sigma_{\mathrm{T}}^2(n)}$$

where:

$r(n)$ is the detector output of the n^{th} symbol;

$g(n)$ is the time varying gain associated with the desired symbol; and

$\sigma_T^2(n)$ is the total noise variance.

6. The method of Claim 5, further comprising determining the variance of multiple access interference analytically.

7. The method of Claim 5, further comprising determining the variance of multiple access interference empirically.

8. The method of Claim 1, further comprising employing multiuser detection to obtain the output of the receiver.

9. A receiver comprising:

a detector to receive transmitted information and provides one or more output symbols based on the transmitted information;

a metric correction section to normalize the one or more output symbols to obtain one or more metrics, the normalization based on a determined variance of multiple access interference; and

a channel decoder to receive the one or more metrics from the metric correction section, the channel decoder to utilize the one or more metrics to decode the transmitted information.

10. The receiver of Claim 9, wherein the detector comprises a multiuser detector.

11. (Previously Presented) The receiver of Claim 9, wherein the detector comprises a rake detector.

12. The receiver of Claim 9, wherein the metric is based on a log likelihood ratio.

13. The receiver of Claim 9, wherein the metric correction section determines one or more normalization factors to apply to the one or more output symbols of the detector.

14. The receiver of Claim 9, wherein the detector comprises a long code CDMA detector.

15. The receiver of Claim 14, wherein the metric correction section is to normalize each output symbol on a symbol by symbol basis with a normalization factor that is independent of the normalization factors of previous symbols.

16. The receiver of Claim 9, wherein the metric is based on a log likelihood ratio for BPSK signaling that is determined from the following equation:

$$LLR(n) = -\frac{2r(n)g(n)}{\sigma_T^2(n)}$$

where:

$r(n)$ is the detector output of the n^{th} symbol;

$g(n)$ is the time varying gain associated with the desired symbol; and

$\sigma_T^2(n)$ is the total noise variance.

17.   The receiver of Claim 16, wherein the variance of the multiple access interference is determined analytically.

18.   The receiver of Claim 16, wherein the variance of the multiple access interference is determined empirically.

19.   A method comprising:

receiving one or more output symbols from a detector;

determining a normalization factor for each of the one or more output symbols, each normalization factor being independent of normalization factors for previous output symbols;

multiplying each of the one or more output symbols by the corresponding normalization factor to obtain a metric correction; and

providing the metric correction for each symbol to a channel decoder.

20.   The method of Claim 19, further comprising decoding a transmission using the metric correction.

21. The method of Claim 19, further comprising determining
the normalization factor based on the following equation:

$$LLR(n) = -\frac{2r(n)g(n)}{\sigma_T^2(n)}$$

where:

r(n) is the detector output of the n^{th} symbol;

g(n) is the time varying gain associated with the desired
symbol; and

$\sigma_T^2(n)$ is the total noise variance.

22. The method of Claim 21, further comprising determining
a variance of a level of multiple access interference
analytically.

23. The method of Claim 21, further comprising determining
a variance of a level of multiple access interference
empirically.

24. A method comprising:

receiving a symbol;

determining a normalization factor for the symbol using a
determined variance in a level of multiple access interference
for the symbol;

normalizing the symbol with the normalization factor; and

providing the normalized symbol to a channel decoder.

25. The method of claim 24, wherein determining the normalization factor comprises:

determining a time varying gain associated with a desired symbol; and

determining the variance in the level of multiple access interference for the symbol.

26. The method of claim 25, wherein determining the normalization factor further comprises determining the variance in a noise term that is independent of the variance in the level of multiple access interference.

27. The method of claim 24, wherein normalizing the symbol with the normalization factor comprises multiplying the symbol by a log likelihood ratio.

28. The method of claim 27, wherein multiplying the symbol by the log likelihood ratio comprises multiplying the symbol by

$$LLR(n) = -\frac{2r(n)g(n)}{\sigma_T^2(n)}$$

where:

r(n) is an output of the symbol;

Applicant: Kobby Pick et al.
Serial No.: 10/053,490
Filed: October 26, 2001
Page: 17 of 19

Attorney's Docket No.: 10559-
454001 / P10771

g(n) is the time varying gain associated with the desired

symbol; and

$\sigma_T^2(n)$ is the total noise variance.

Applicant: Kobby Pick et al.   Attorney's Docket No.: 10559-
Serial No.: 10/053,490   454001 / P10771
Filed: October 26, 2001
Page: 18 of 19

(9) Evidence Appendix

No evidence is submitted herewith.

Applicant: Kobby Pick et al.   Attorney's Docket No.: 10559-
Serial No.: 10/053,490   454001 / P10771
Filed: October 26, 2001
Page: 19 of 19

(10) Related Proceedings Appendix

No related proceedings are submitted herewith.